



Turn ordinary sports broadcasts and movies into extraordinary entertainment in the comfort of your own home. A three-LCD imaging device provides superior image accuracy for brilliant, big screen performance at a truly astonishing value. A native16:9 aspect ratio with Epson 0.55" wide-panel LCDs combined with a maximum 700:1 contrast ratio facilitates an authentic theater experience.

Fill a 100" screen from only 8 feet back with the newly designed lens and 1.54x zoom ratio. This quiet, 1000 ANSI lumen projector offers home entertainment at its best. Four projection modes mean great color detail from any source material.* And, it's all at your fingertips with the convenient remote control. No installation is required—all you need is a coffee table and a wall. And, at 7.9 lbs., it's portable enough to take and share with friends and family.

Remarkable image quality and performance

- Wide-panel display (16:9 aspect ratio) for larger-than-life images and HDTV
- Three Epson 0.55" wide high-aperture LCDs for rich color saturation and broad color gamut
- 700:1 maximum contrast ratio for blacker blacks and whiter whites
- 480p (854 x 480) resolution for sharp, vivid detail
- Specialized video processor for clear, sharp images
- Four selectable projection modes (Dynamic, Living room, Theatre and Theatre black) whatever the room environment or source material
- Electronic cinema filter built in to enhance video images, especially dark scenes
- Renowned Epson reliability ensures a quality product

Easy setup and operation


- Easy cable connection to a DVD player, camcorder, digital set-top box/cable, VCR, video game console or PC
- Convenient remote control that's stored within the projector
- Long lamp life—2000-3000 hours depending on the color mode used
- Whisper-quiet operation to eliminate distracting fan noise
- 1W speaker for small audiences
- Start Here Kit gets first time users projecting in just minutes
- 20-second cool down and 10-second start up time
- Child lock for added security and safety

Outstanding Epson service and support

- 2-year Epson limited warranty
- Epson PrivateLineSM dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday - Friday (calls are promptly answered live)
- Epson Home Service Program provides a replacement projector, typically the next business day
- 90-day bulb warranty for added dependability



Front View



Epson PowerLite Home 10 Specifications

Projection System	Epson original LCD prism technology
Projection Method	Front/rear/ceiling mount
LCD Size Driving method Pixel number Native resolution Aspect ratio Pixel arrangement	0.55" wide Poly-silicon TFT Active Matrix 854 x 480 pixels 480p 16:9 Stripe
Projection Lens Type F-number Focal length Zoom ratio	Manual: zoom/focus - optical 1.7 to 2.1 13.9 - 21.4mm 1-1.54x
Lamp Type Life (typical)* Screen Size (projected of	132W UHE User Replaceable Lamp 3000H (Color mode: Theatre Black) 2000H (Color mode: other color modes)
Wide Tele	30" to 300"(2.4' to 24.9') 30" to 300"(3.7' to 38.2')
Keystone Correction	Vertical ±15°
Brightness (typical)	1000 ANSI Im (Color mode: Dynamic)
Contrast Ratio	700:1 (Color mode: Theatre Black)
Brightness Uniformity (typical) 90%
Color Reproduction	Full color (16.7 mil)
Sound Output	1w Monaural speaker
Effective Scanning Freq Pixel Clock Horizontal Vertical	uency Range 13.5MHz to 162MHz 15KHz to 92KHz 50Hz to 85Hz
Adjustment Function Tilt angle	0° to 10°
RGB	Analog RGB I/O
Display performance Resize Video Audio	1024 x 768/800 x 600/640 x 480 Mini D-sub 15pin x1 Blue-molding RCA x 2 (White/Red)
Video I/O Display performance	NTSC: 480 line PAL: 480 line
Input signal Video standard	NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/ SECAM (Composite video/S video) 480/575i/480p/575p/720p/ 1080i (Component video)
Video Input Composite video S-Video Component Video Video RGB	RCA (Yellow) x 1 Mini DIN RCA x 3 (Red, Green, Blue) RCA x 4 (In common with Component Video and Composite Video)

Control I/O	
Serial I/O	
I/O terminal	Mini D-sub 9pin x 1
I/O signal	RS-232c

Input terminal

Remote control Card type

Operating Temperature Cool-down period Start-up period	41°F to 95°F (5°C to 35°C) Approx. 20 sec Approx. 10 sec
Power Supply Voltage	100-240VAC ±10%, 50/60Hz
Power Consumption	200W, 5W at standby mode
Dimensions (includes lens and feet)	11.6"D x 15.8"W x 4.8"H
Dimensions (excludes lens and feet)	11.6"D x 15.8"W x 4.5"H
Weight	Approx. 7.9 lb
Fan Noise Normal mode (Dynamic, Living Room, Theatre) Quiet mode (Theatre Black)	35dB 29dB

Warranty

Standard two year parts and labor limited warranty, 90-day lamp warranty, Epson Home Service Program and Epson PrivateLine dedicated toll-free support (U.S. and Canada only)

Supplied Accessories

Power cord, remote control, lithium CR2025 battery, and Owner's Manual

Tower cord, remote control, lithlam CN2023 battery, and owner 3 Mandai		
Product/Accessory Part Numbers		
Epson PowerLite Home 10	V11H127020	
Replacement lamp (ELPLP25H)	V13H010L2H	
Samsonite wheeled softcase	ELPKS35	
Samsonite soft shoulder case	ELPKS43	
Air filter set (ELPAF04)	V13H134A04	
Replacement remote (ELPST12)	V12H007T12	
50" portable 4:3 pop-up screen (ELPSC06)	V12H002S06	
60" portable 4:3 pop-up screen (ELPSC07)	V12H002S07	
80" portable 4:3 pop-up screen (ELPSC08)	V12H002S08	
Mac adapter set	ELPAP01	
Ceiling mount	ELPMB42	
Suspension adapter	ELPMBAPL	
False ceiling plate	ELPMBFCP	
S-video cable	ELPSV01	
Support–The Epson Connection sM		
Pre-Sales Support U.S. and Canada	800-463-7766	
Automated Technical Support	800-922-8911	
Internet Web Site	www.enson.com	

^{*} Lamp life results will vary depending upon mode selected, environmental conditions, and usage.

EPSON

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5